

## Product presentaion

### CAR SPEAKER

#### FULL RANGE SPEAKER



##### S-1041 (4 inches)

Power RMS.....25W  
Power max.....80W  
Impedance.....4Ohm  
Frequency Response.....120Hz-15kHz  
Sensitivity.....88dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....115mm  
Mounting depth.....40mm



##### S-1051 (5 inches)

Power RMS.....25W  
Power max.....80W  
Impedance.....4Ohm  
Frequency Response.....100Hz-15kHz  
Sensitivity.....89dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....138mm  
Mounting depth.....36mm



##### S-1061 (6.5 inches)

Power RMS.....25W  
Power max.....80W  
Impedance.....4Ohm  
Frequency Response.....80Hz-15kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....142mm  
Mounting depth.....43mm

#### COAXIAL SPEAKER



##### S-2041 (4 inches)

Power RMS.....30W  
Power max.....100W  
Impedance.....4Ohm  
Frequency Response.....120Hz-20kHz  
Sensitivity.....88dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....115mm  
Mounting depth.....40mm



##### S-2051 (5 inches)

Power RMS.....30W  
Power max.....120W  
Impedance.....4Ohm  
Frequency Response.....100Hz-20kHz  
Sensitivity.....89dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....138mm  
Mounting depth.....36mm



##### S-2651 (6.5 inches)

Power RMS.....30W  
Power max.....150W  
Impedance.....4Ohm  
Frequency Response.....80Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....142mm  
Mounting depth.....43mm

## Product presentaion

### CAR SPEAKER

#### COAXIAL SPEAKER



##### S-2042 (4 inches)

Power RMS.....30W  
Power max.....100W  
Impedance.....4Ohm  
Frequency Response.....100Hz-20kHz  
Sensitivity.....89dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....115mm  
Mounting depth.....40mm



##### S-2052 (5 inches)

Power RMS.....25W  
Power max.....80W  
Impedance.....4Ohm  
Frequency Response.....100Hz-15kHz  
Sensitivity.....89dB/W(1m)  
Voice Coil.....ASV20.4  
Mounting Diameter.....138mm  
Mounting depth.....36mm



##### S-2652 (6.5 inches)

Power RMS.....45W  
Power max.....150W  
Impedance.....4Ohm  
Frequency Response.....65Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....155mm  
Mounting depth.....60mm

#### COAXIAL SPEAKER



##### S-2043 (4 inches)

Power RMS.....30W  
Power max.....100W  
Impedance.....4Ohm  
Frequency Response.....100Hz-20kHz  
Sensitivity.....88dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....116mm  
Mounting depth.....44mm



##### S-2053 (5 inches)

Power RMS.....35W  
Power max.....120W  
Impedance.....4Ohm  
Frequency Response.....90Hz-20kHz  
Sensitivity.....89dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....138mm  
Mounting depth.....54mm



##### S-2653 (6.5 inches)

Power RMS.....50W  
Power max.....150W  
Impedance.....4Ohm  
Frequency Response.....65Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....155mm  
Mounting depth.....60mm

## Product presentaion

### CAR SPEAKER

#### COMPONENT SPEAKER SYSTEM



**S-3651 (6.5 inches)**  
Power RMS.....45W  
Power max.....130W  
Impedance.....4Ohm  
Frequency Response.....65Hz-20kHz  
Sensitivity.....91dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....155mm  
Mounting depth.....60mm



**S-3652 (6.5 inches)**  
Power RMS.....45W  
Power max.....130W  
Impedance.....4Ohm  
Frequency Response.....65Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....155mm  
Mounting depth.....67mm



**S-3653 (6.5 inches)**  
Power RMS.....50W  
Power max.....130W  
Impedance.....4Ohm  
Frequency Response.....65Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....ASV25.5  
Mounting Diameter.....155mm  
Mounting depth.....70mm



**S-4651 (6.5 inches)**  
Power RMS.....60W  
Power max.....200W  
Impedance.....4Ohm  
Frequency Response.....60Hz-20kHz  
Sensitivity.....90dB/W(1m)  
Voice Coil.....TIL25.5  
Mounting Diameter.....155mm  
Mounting depth.....70mm