

ELECTRIC BRAKE LEVERS /



240PDD /



稳定的压铸生产工艺；隐藏线设计风格；可独立安装的机械铃铛；优质线性霍尔开关，性能可靠。

Stable die-casting production process; Hidden line design style; Mechanical bells that can be independently installed; High-quality linear Hall switches with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L157mm W118mm H31mm	电流 /Current	12V/3A
重量 /Weight	131g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	100,000 mating cycle



NEW



240PDD/2.A /



稳定的压铸生产工艺；经典的流线型设计风格；优质机械开关，性能可靠。Stable die-casting production process; Classic streamline design style; High-quality mechanical switch with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L 157mm W 118mm H 31mm	电流 /Current	12V/3A
重量 /Weight	131g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	100,000 mating cycle



138PDD /



稳定的压铸生产工艺；球头把手，符合新国标；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever, in line with the new national standard; High-quality mechanical switch, reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L188mm W108mm H34mm	电流 /Current	12V/3A
重量 /Weight	135g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



132PDD /



稳定的压铸生产工艺；球头把手，符合新国标；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever, in line with the new national standard; High-quality mechanical switch, reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L178mm W105mm H34mm	电流 /Current	12V/3A
重量 /Weight	135g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



128P+BS116.A /



稳定的压铸生产工艺；后视镜孔安装设计；球头把手，符合新国标；优质机械开关，性能可靠。Stable die-casting production process; Rearview mirror hole installation design; Ball-end lever, in line with the new national standard; High-quality mechanical switch, reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L208mm W112mm H34mm	电流 /Current	12V/3A
重量 /Weight	135g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



122PDD /



稳定的压铸生产工艺；超长把手；带后视镜安装孔；优质机械开关，性能可靠。Stable die-casting production process; Extra long lever; With mounting holes for rear-view mirrors; High-quality mechanical switches with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L202mm W115mm H34mm	电流 /Current	12V/3A
重量 /Weight	130g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



112PDD /



稳定的压铸生产工艺；超长把手；优质机械开关，性能可靠。Stable die-casting production process; Extra long lever; High-quality mechanical switch with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L170mm W102mm H34mm	电流 /Current	12V/3A
重量 /Weight	115g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



108PDD.A /



稳定的压铸生产工艺；带软垫把手，手感更舒适；优质机械开关，性能可靠。Stable die-casting production process; With padded lever, more comfortable feel; High-quality mechanical switch, reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L 156mm W 105mm H 34mm	电流 /Current	12V/3A
重量 /Weight	120g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX6	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



108P/2.A /



稳定的压铸生产工艺；后视镜孔安装设计；优质机械开关，性能可靠。Stable die-casting production process; Rear-view mirror hole installation design; High-quality mechanical switch with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L 156mm W 102mm H 34mm	电流 /Current	12V/3A
重量 /Weight	131g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



106PDD.A /



稳定的压铸生产工艺；经典的流线型设计风格；优质机械开关，性能可靠。Stable die-casting production process; Classic streamline design style; High-quality mechanical switch with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2 Pins
尺寸 /Size	L 156mm W 102mm H 34mm	电流 /Current	12V/3A
重量 /Weight	125g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle



271PDD.A+BS141.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L182.5mm W112mm H35.5mm	电流 /Current	12V/3A
重量 /Weight	115.24g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



271PDD.A+BS143.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L182.5mm W112mm H35.5mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



255PDDZ.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠；机械驻车功能。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance; Mechanical parking function.

尺寸 /Size	L174mm W127.5mm H37mm	电流 /Current	12V/3A
重量 /Weight	115g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



241PDD.A+BS197/2.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L158mm W35.5mm H104mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



241PDD.A+BS185/2.A /

稳定的压铸生产工艺；超长把手；优质机械开关，性能可靠。
Stable die-casting production process; Extra long lever; High-quality mechanical switch with reliable performance.

尺寸 /Size	L158mm W35.5mm H104mm	电流 /Current	12V/3A
重量 /Weight	120g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



231PDD /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L183mm W126mm H42mm	电流 /Current	12V/3A
重量 /Weight	120g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



223PDD/5.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L168mm W116.5mm H38.5mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



137PDD/3+BS179/2 /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L180.5mm W114mm H62.5mm	电流 /Current	12V/3A
重量 /Weight	115.24g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX7	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



135PDD+BS177/3.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L152.5mm W103mm H39mm	电流 /Current	12V/3A
重量 /Weight	115g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		

NEW



259PDD+LD06 /



稳定的压铸生产工艺；隐藏线设计风格；可独立安装的机械铃铛；优质线性霍尔开关，性能可靠。
Stable die-casting production process; Hidden line design style; Mechanical bells that can be independently installed;
High-quality linear Hall switches with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2Pins
尺寸 /Size	L152mm W102mm H59mm	电流 /Current	12V/3A
重量 /Weight	125g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	100,000 mating cycle

NEW



259PDD.A+LD259.A /

稳定的压铸生产工艺；隐藏线设计风格；可独立安装的机械铃铛；优质线性霍尔开关，性能可靠。
Stable die-casting production process; Hidden line design style; Mechanical bells that can be independently installed;
High-quality linear Hall switches with reliable performance.

标准 /Approval	RoHS	芯线 /Wiring	2Pins
尺寸 /Size	L152mm W102mm H59mm	电流 /Current	12V/3A
重量 /Weight	125g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	100,000 mating cycle

NEW



84PDD/2.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。
Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L179mm W133mm H36mm	电流 /Current	12V/3A
重量 /Weight	115.24g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,000 mating cycle
芯线 /Wiring	2 Pins		



47PDD.A /

稳定的压铸生产工艺；经典的流线型设计风格；优质机械开关，性能可靠。Stable die-casting production process; Classic streamline design style; High-quality mechanical switch with reliable performance.

尺寸 /Size	L154mm W119.5mm H32.5mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



47PDD.A+BS47/2.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L154mm W119.5mm H32.5mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



49PDD /

稳定的压铸生产工艺；经典的流线型设计风格；优质机械开关，性能可靠。Stable die-casting production process; Classic streamline design style; High-quality mechanical switch with reliable performance.

尺寸 /Size	L128mm W115mm H35.5mm	电流 /Current	12V/3A
重量 /Weight	105g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



49PDD.A+BS49/2.A /

稳定的压铸生产工艺；经典的流线型设计风格；优质机械开关，性能可靠。Stable die-casting production process; Classic streamline design style; High-quality mechanical switch with reliable performance.

尺寸 /Size	L128mm W115mm H35.6mm	电流 /Current	12V/3A
重量 /Weight	107.85g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



67PDD/3.A+BS68.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance.

尺寸 /Size	L168.7mm W117.3mm H31mm	电流 /Current	12V/3A
重量 /Weight	108g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		



67PDDZ/2.A+BS193/2.A /

稳定的压铸生产工艺；球头把手；优质机械开关，性能可靠；机械驻车功能。Stable die-casting production process; Ball-end lever; High-quality mechanical switch, reliable performance; Mechanical parking function.

尺寸 /Size	L161.5mm W115.5mm H38.5mm	电流 /Current	12V/3A
重量 /Weight	105g	工作温度 /Operating Temperature	-20°C~ 60°C
防水 /Waterproof	IPX5	抗拉力 /Stretching Resistance	≥450N
材料 /Material	Aluminum alloy	耐久性 /Durability	10,0000 mating cycle
芯线 /Wiring	2 Pins		